

## Index Plungers · with rapid locking head

22122.0315



### Product Description

Index plungers are used for indexing bores.

#### Material

##### Body

- Stainless steel 1.4305

##### Press button

- Thermoplastic POM, red

##### Locking pin

- Stainless steel 1.4305, nickel-plated

##### Knob

- Thermoplastic PA 6, black-grey, matt

#### Assembly

The screw length can be adapted by distance collars for index plungers (EH 22120.).

#### Operation

The locking pin is drawn in and locked by pulling the knob. The projecting red press button indicates the locking position (locking pin drawn in). Pushing the red press button causes the locking pin to jump back into the locking position.

#### More information



#### Notes

Knob not removable.  
Lock nuts have to be purchased separately.

#### Further products

- Locating Bushings, for index bolts and index plungers
- Distance Collars, for index plungers
- Mounting Blocks, for index bolts and index plungers

### Drawing





lock nut  
22120.0116 - .0118 (Steel)  
22120.0516 - .0518 (Stainless steel)

### Order information

Dimensions							WS	Spring load <sup>1)</sup>		Temperature		Art. No.	
d <sub>1</sub>	d <sub>2</sub>	l <sub>2</sub> min.	d <sub>3</sub>	l <sub>1</sub> ~	l <sub>3</sub>	l <sub>4</sub>	WS	F <sub>1</sub> ~	F <sub>2</sub> ~	min.	max.		
[mm]							[mm]	[N]		[°C]		[g]	
-0.02 -0.04													
<b>Stainless steel</b>													
8	M16 x 1,5	8	30	59.5	26	8	19	8.5	26	-30	80	75	<a href="#">22122.0315</a>

<sup>1)</sup> statistical average value

Accessories

	Dimensions d <sub>2</sub> [mm]	Wrench size [mm]	 [g]	Art. No.
<b>Stainless steel</b>				
	M16 x 1,5	24	15.0	22120.0518

Compliance

**RoHS compliant**

Compliant according to Directive 2011/65/EU and Directive 2015/863.

**Does not contain SVHC substances**

No SVHC substances with more than 0.1% w/w contained - SVHC list [REACH] as of 23.01.2024.

**Does not contain Proposition 65 substances**

No Proposition 65 substances included.  
<https://www.P65Warnings.ca.gov/>

**Free from Conflict Minerals**

This product does not contain any substances designated as "conflict minerals" such as tantalum, tin, gold or tungsten from the Democratic Republic of Congo or adjacent countries.