# Ball Lock Pins · self-locking, with combination handle, precipitation-hardened



### **Product Description**

For quick fastening, locking, adjusting, changing and securing. Quickly and easily unlockable for frequently repeated connections.

All versions are corrosion resistant. When using stainless steel 1.4542: high-strength, hardened, abrasion resistant pin with high load capacity.

Ergonomic grip, different colour combinations available. The grip design provides protection of unintentional unlocking.

#### Material

#### Pin part

· Stainless steel 1.4542, precipitationhardened

### Handle

• Thermoplastic PA 6 grey / orange

· Stainless steel

### **Operation**

The balls are unlocked by pressing the button.

#### Characteristic

Types from stainless steel 1.4542 with marking below the balls.

### More information

#### **Notes**

Customized design on request.

### References

Stainless steel 1.4305, see EH 22370.

#### **Accessories**

Can easily be fitted with retaining cable EH 22400.

### **Further products**

- · Ball Lock Pins, self-locking, with combination handle
- Locating Bushings, for ball lock pins and socket pins
- Locating Bushings, with flange, for ball lock pins and socket pins
- **Retaining Cables**
- Positioning Bushings, with collar, DIN 172 A
- Positioning Bushings, without collar, DIN 179 A

### **Drawing**



Halder France SAS

\*\* Types from stainless steel 1.4542 with marking

www.halder.fr Page 1 of 3 Published on: 19.11.2024

## **Order information**

| Dimensions                              |                        |                |                |      |                      |                |      | Location    | Shearing resistance,         |      |      | I   | Art. No.   |
|---|------------------------|----------------|----------------|------|----------------------|----------------|------|-------------|------------------------------|------|------|-----|------------|
| <b>d</b> <sub>1</sub><br>-0.04<br>-0.08 | l <sub>1</sub><br>+0.6 | d <sub>2</sub> | d <sub>3</sub> | d₄   | l <sub>2</sub><br>±1 | l <sub>3</sub> | 14   | hole<br>H11 | two-shear <sup>1)</sup> min. | min. | max. |     |            |
| [mm]                                    |                        |                |                |      |                      |                |      | [mm]        | [kN]                         | [°C] |      | [g] |            |
| Handle colour: orange                   |                        |                |                |      |                      |                |      |             |                              |      |      |     |            |
| 16                                      | 70                     | 19             | 47.6           | 25.2 | 14                   | 39.7           | 16.7 | 16          | 257                          | -30  | 80   | 194 | 22380.0234 |

<sup>1)</sup> Shearing resistance similar to DIN 50141

# **Application example**





Page 2 of 3 Published on: 19.11.2024

www.halder.fr



## Compliance

### **RoHS** compliant

Compliant according to Directive 2011/65/EU and Directive 2015/863.

### **Does not contain SVHC substances**

No SVHC substances with more than 0.1% w/w contained - SVHC list [REACH] as of 27.06.2024.

### Does not contain Proposition 65 substances

No Proposition 65 substances included. https://www.P65Warnings.ca.gov/

### **Free from Conflict Minerals**

This product does not contain any substances designated as "conflict minerals" such as tantalum, tin, gold or tungsten from the Democratic Republic of Congo or adjacent countries.



Page 3 of 3 Published on: 19.11.2024