# Ball-Ended Thrust Screws • headless, round ball

# 22720.0756



## **Product Description**

Ball-ended thrust screws with thermoplastic ball are used for pressure sensitive pieces. Ball-ended thrust screws can also be used for positioning and clamping, tightening or supporting of non-parallel surfaces.

#### **Material**

#### Ball

· Stainless steel, hardened

#### Screw

· Stainless steel 1.4305

### More information

#### Notes

Ball not secured against rotating. Customized design on request.


#### References

Thread lock on request, please refer to appendix - Technical Data -

#### **Further products**

- Ball-Ended Thrust Screws, headless, with fine-pitch thread
- Ball-Ended Thrust Screws, headless, round ball and hexalobular socket

## **Drawing**




### Order information

Dimensions			ws	Load capacity	<u>D</u>	Ĭ	Art. No.
d <sub>1</sub>	l <sub>1</sub>	Ball diameter		for static load <sup>1)</sup> max.	max.		
[mm]			[mm]	[kN]	[°C]	[g]	
round ball, Stainless steel							
M4	12	2.5	2	3.5	250	0.7	22720.0756

<sup>1)</sup> Statements on load capacity are not valid for the stainless steel type (except the type fitted with thermoplastic balls).

## **Application example**



Halder France SAS

www.halder.fr Page 1 of 2

Published on: 19.11.2024

## Compliance

## **RoHS** compliant

Compliant according to Directive 2011/65/EU and Directive 2015/863.

## Does not contain SVHC substances

No SVHC substances with more than 0.1% w/w contained - SVHC list [REACH] as of 27.06.2024.

### **Does not contain Proposition 65 substances**

No Proposition 65 substances included. https://www.P65Warnings.ca.gov/

### **Free from Conflict Minerals**

This product does not contain any substances designated as "conflict minerals" such as tantalum, tin, gold or tungsten from the Democratic Republic of Congo or adjacent countries.



www.halder.fr Page 2 of 2

Published on: 19.11.2024