SIMPLEX soft-face mallets • Superplastic / nylon; with cast iron housing and high-quality wooden handle

EH 3078.





Product Description

The SIMPLEX series 3078 comes with the insert combination of superplastic / nylon. The superplastic insert (series 3207) is a medium hard plastic insert made of extruded and extremely homogeneous material. Compared to injection moulded plastic inserts, it is therefore considerably more wear-resistant and durable.

The nylon insert (series 3208) offers outstanding impact qualities and is guaranteed to combine maximum strength with unique durability. It is composed of extruded and extremely homogeneous material and will not chip even at temperatures below zero. Moreover, it is also oil and grease resistant.

Made of cast iron, the housing comes with an integrated handle protection sleeve that provides for a high level of break resistance.

Damping vibrations and shaped ergonomically, the high-quality wooden handle has a double coat of varnish in the grip area and is thus resistant to dirt.

In line with the smart SIMPLEX principle, all components are replaceable and can be retrofitted. This translates to savings in both money and resources.

This version is available in sizes ranging from D30mm to D80mm and as a sledge hammer (3078.081)

Product features:

- SIMPLEX soft-face mallet with the insert combination of superplastic (white, medium hard, very durable) / nylon (white, hard, very wear-resistant, no chipping even in sub-zero temperatures, oil and grease resistant).
- · Cast iron housing with integrated handle protection sleeve and excellent break resistance.
- High-quality, vibration-damping, and ergonomically shaped wooden handle; grip area with double coat of varnish (resistant to dirt).
- All parts can be replaced / retrofitted, resulting in great savings in cost and resources.
- Available in sizes ranging from D30mm to D80mm and as a sledge hammer (3078.081).

Application Areas

Adjusting of workpieces, assembly of sharp-edged workpieces, housing assembly, mould construction, plant construction, hall construction, steel construction, exhibition stand construction, sheet-metal forming, repair and maintenance work

Material

Handle

• Wood

insert 1

- · Superplastic, white
- Medium hard
- · Very durable
- Wear-resistant

insert 2

- · Nylon, white
- hard
- · Very wear-resistant
- · no chipping (even at tempeatures below
- zero)
- · Oil and grease resistant
- Housing
- Cast iron

Order information

Dimensions				Ĩ	GTIN	proficl@ss	ecl@ss 10.1	Art. No.
ø	i ‡		Length x Width x Height	-		5.0		
[mm]			[9]					
30	90	295	295 x 90 x 30	333	4030618304661	AAA905c002	21-04-09-16	3078.030
40	115	325	325 x 115 x 40	607	4030618302568	AAA905c002	21-04-09-16	3078.040
50	135	370	370 x 135 x 50	1123	4030618302575	AAA905c002	21-04-09-16	3078.050
60	150	405	405 x 150 x 60	1483	4030618302582	AAA905c002	21-04-09-16	3078.060
80	175	490	490 x 175 x 80	3009	4030618302599	AAA905c002	21-04-09-16	3078.080

Compliance

RoHS compliant

Compliant according to Directive 2011/65/EU and Directive 2015/863.

Does not contain SVHC substances

No SVHC substances with more than 0.1% w/w contained - SVHC list [REACH] as of 27.06.2024.

Does not contain Proposition 65 substances

No Proposition 65 substances included. https://www.P65Warnings.ca.gov/

Free from Conflict Minerals

This product does not contain any substances designated as "conflict minerals" such as tantalum, tin, gold or tungsten from the Democratic Republic of Congo or adjacent countries.